



US009925828B2

(12) **United States Patent**
Koziatek

(10) **Patent No.:** **US 9,925,828 B2**
(45) **Date of Patent:** ***Mar. 27, 2018**

(54) **BICYCLE WHEEL RIM**

(71) Applicant: **K.G. Motors, Inc.**, Horseheads, NY (US)

(72) Inventor: **Stanley F. Koziatek**, Big Flats, NY (US)

(73) Assignee: **K.G. Motors, Inc.**, Horseheads, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/482,091**

(22) Filed: **Apr. 7, 2017**

(65) **Prior Publication Data**

US 2017/0210163 A1 Jul. 27, 2017

Related U.S. Application Data

(63) Continuation of application No. 14/859,591, filed on Sep. 21, 2015, now Pat. No. 9,649,878, which is a (Continued)

(51) **Int. Cl.**
B60B 21/02 (2006.01)
B60B 1/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B60B 21/025** (2013.01); **B60B 1/003** (2013.01); **B60B 1/02** (2013.01); **B60B 21/026** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC B60B 21/00; B60B 21/02; B60B 21/025; B60B 21/026; B60B 21/028; B60B 21/04;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,194,177 A 8/1916 Henderson
1,316,773 A 9/1919 Daigre
(Continued)

OTHER PUBLICATIONS

International Organization for Standardization. "Bicycle tyres and rims—Part 1: Tyre designations and dimensions." 5th edition (Dec. 12, 1997). (14 pages).

(Continued)


Primary Examiner — Jason Bellinger

(74) *Attorney, Agent, or Firm* — Wilmer Cutler Pickering Hale and Dorr LLP

(57) **ABSTRACT**

A bicycle wheel rim having a circular base portion including a proximal surface and a distal surface, and a pair of integral sidewalls extending generally radially outward from an intersection region of the proximal surface and the distal surface. The distal surface of the rim has a central hump, a trough contiguous with the central hump extending axially outward from the hump, and a flat shelf immediately adjacent, contiguous with, and extending axially outward from the trough. Another embodiment of the invention is directed to a bicycle wheel including the embodied rim, a plurality of spokes engaged at respective ends thereof with the rim and a hub engaged with the plurality of spoke members at opposite ends thereof. Another embodiment of the invention is directed to a bicycle wheel assembly comprising the embodied wheel and a tube and/or tire mounted on the rim.

26 Claims, 4 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/089,173, filed on Nov. 25, 2013, now Pat. No. 9,162,524, which is a continuation of application No. 13/219,340, filed on Aug. 26, 2011, now Pat. No. 8,613,485, which is a continuation of application No. 12/420,595, filed on Apr. 8, 2009, now Pat. No. 8,007,053, which is a continuation of application No. 12/197,901, filed on Aug. 25, 2008, now abandoned, which is a continuation of application No. 11/965,153, filed on Dec. 27, 2007, now abandoned, which is a continuation of application No. 10/959,743, filed on Oct. 6, 2004, now Pat. No. 7,334,846.

(51) **Int. Cl.**

B60B 21/10 (2006.01)
B60B 1/02 (2006.01)
B60B 21/06 (2006.01)

(52) **U.S. Cl.**

CPC **B60B 21/028** (2013.01); **B60B 21/062** (2013.01); **B60B 21/102** (2013.01)

(58) **Field of Classification Search**

CPC B60B 21/10; B60B 21/102; B60B 21/104; B60B 21/106; B60C 7/24; B60C 17/04; B60C 17/041; B60C 17/042
 See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

1,551,445 A 8/1925 Wagenhorst
 4,896,921 A 1/1990 Sato et al.
 6,089,672 A 7/2000 Chen
 6,155,651 A 12/2000 Mizata et al.

6,183,047	B1	2/2001	Kuhl	
6,237,662	B1	5/2001	Thomasberg	
6,283,557	B1	9/2001	Okajima et al.	
6,402,255	B1	6/2002	Chen	
6,402,256	B1	6/2002	Mercat et al.	
6,409,279	B1	6/2002	Chen	
6,428,115	B1	8/2002	Chen et al.	
6,457,501	B1	10/2002	Ball	
6,568,766	B1	5/2003	Okajima et al.	
6,736,462	B1	5/2004	Okajima	
6,752,187	B1	6/2004	Tien et al.	
6,761,847	B2	7/2004	Meggiolan	
6,767,069	B2	7/2004	Chen	
6,767,070	B1	7/2004	Chiang et al.	
6,776,460	B1	8/2004	Lo	
6,817,680	B2	11/2004	Chen	
6,938,962	B1	9/2005	Schlanger	
7,083,239	B2	8/2006	Okajima	
7,090,307	B2	8/2006	Okajima	
7,104,300	B2	9/2006	Veux et al.	
7,334,846	B2 *	2/2008	Koziatek	B60B 21/025
				152/382
8,007,053	B2 *	8/2011	Koziatek	B60B 21/025
				152/382
8,613,485	B2 *	12/2013	Koziatek	B60B 21/025
				152/382
9,162,524	B2 *	10/2015	Koziatek	B60B 21/025
9,649,878	B2 *	5/2017	Koziatek	B60B 21/025
2003/0025383	A1	2/2003	LaCombe et al.	
2003/0150538	A1	8/2003	Ceretta	
2004/0004391	A1	1/2004	Fioravanti	
2004/0095014	A1	5/2004	Veux et al.	
2004/0222691	A1	11/2004	Okajima	

OTHER PUBLICATIONS

International Organization for Standardization. "Bicycle tyres and rims—Part 2: Rims." 2nd edition (Dec. 1, 1996). (20 pages).

* cited by examiner




FIG. 1
Prior Art




FIG. 2




FIG.3




FIG.4




FIG. 5




FIG. 6





FIG. 7



1

BICYCLE WHEEL RIM

This application is a continuation of U.S. application Ser. No. 14/859,591, filed Sep. 21, 2015, now U.S. Pat. No. 9,649,878, which is a continuation of U.S. application Ser. No. 14/089,173, now U.S. Pat. No. 9,162,524, filed Nov. 25, 2013, which is continuation of U.S. application Ser. No. 13/219,340, now U.S. Pat. No. 8,613,485, filed Aug. 26, 2011, which is a continuation of U.S. application Ser. No. 12/420,595, now U.S. Pat. No. 8,007,053, filed Apr. 8, 2009, which is a continuation of U.S. application Ser. No. 12/197,901, filed Aug. 25, 2008, abandoned, which is a continuation of U.S. application Ser. No. 11/965,153, filed Dec. 27, 2007, abandoned, which is a continuation of U.S. application Ser. No. 10/959,743 filed Oct. 6, 2004, now U.S. Pat. No. 7,334,846, the entireties of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

Embodiments of the invention are directed to the field of bicycle wheel rims and, more particularly, to a lighter, stronger and otherwise improved rim for tires with or without tubes.

2. Description of Related Art

The rim is the outer, usually metal, hoop of a bicycle wheel. The spokes of a bicycle wheel extend between a central hub of the wheel and the rim. An inflatable tube and/or tire are positioned around the exterior of the rim and air is introduced through a valve mechanism to inflate the tube and/or tire on the rim as a functional part of a bicycle.

A prior art rim including a mounted, inflated tire is shown in cross section in FIG. 1 to illustrate conventional rim construction. The rim **100** has a base portion **101**, which holds the distal portion of a spoke assembly **102**. The base portion extends upward in the form of a Y to a point **103**. A mounting surface **104** of the rim has a generally concave profile and extends between, and connects to, opposing points **103**. Sidewalls **105** extend outwards from points **103** and terminate in bead lock region **106**. Tire **110** has tire bead regions **112**. In an uninflated state, the tire bead regions **112** loosely rest on rim surface **104** in the region between sidewalls **105**. Upon inflation, the bead portions ride up the surface **104** until they sealingly engage sidewalls **105**. Due to the construction of the tire bead **112**, the bead lock regions **106** help to stabilize the engagement of the tire with the rim. Many variations of rim designs are known to those skilled in the art. However, the great majority of rims will have the basic portions illustrated in FIG. 1.

The dimensions of various portions of a bicycle rim can significantly influence rim function. For example, weight is a significant consideration in a racing or touring rim. In addition to material considerations, rim parameters such as the inside distance between the rim sidewalls will largely determine useable tire size, the ability to use an inner tube within the tire, rim strength, the effect of forces on the rim during various maneuvers such as turning, braking, etc., and others. The shape of the surface **104** may significantly influence the ease of tube/tire mounting and tube/tire inflation. The height, shape and thickness of the rim sidewalls will contribute to overall rim weight, strength, tire stability, air leakage, and other considerations appreciated by those skilled in the art.

Several issues can be identified with respect to conventional rim construction and dimensions. Rim sidewalls typically have a height dimension, shown as H in FIG. 1,

2

between about 0.225 inch to ≥ 0.265 inch for a conventional bicycle rim. As the dimension H increases, so does the mechanical leverage of the tire on the rim. The greater leverage resulting from a higher sidewall further increases the forces acting in the region of point **103** of the rim shown in FIG. 1, thus requiring additional support at points **103** in the form of more material and increased rim weight. A higher sidewall dimension, H, promotes greater flexing of the rim and may result in cracking or stress fracture of the rim material. In addition, as rim sidewall height, H, increases, available tire inflation volume decreases while inflation pressure increases. Moreover, less tire surface is available resulting in decreased traction and other disadvantages. Another consequence of high sidewalls and various head lock sizes and shapes is the well known "pinch flat" or "snake bite" that may be caused when the tube or tire gets pinched between the rim and a hard, sharp object such as a rock, curb stone or the edge of a pothole, for example. An under-inflated tire also contributes to a pinch flat occurrence. A too soft, or too narrow (for the rim) tire more easily lets the tire bottom out when striking an obstruction resulting in the pinch holes from the bead locks or distal portion of the sidewall.

Several issues to be considered with respect to rim surface **104** as shown in FIG. 1 include rim strength, the ability to uniformly position the tire bead region on the rim prior to inflation and the ease of tire inflation, particularly with a manual pump, the interchangeable use of tubes and/or tubeless tires, and others recognized in the art. In light of the known shortcomings of conventional bicycle rim designs, such as those set forth above and others known to those skilled in the art, the inventor has recognized a need for an improved rim that addresses these disadvantages and additionally results in a lighter, stronger, more versatile, better performing and cost effective rim for the rider.

SUMMARY OF THE INVENTION

An embodiment of the invention is directed to a bicycle wheel rim. The rim is intended to have an inner tube and/or a tire mounted onto the rim. The rim has a circular base portion consisting of a proximal surface (i.e., the surface facing the wheel hub, which as part of a wheel assembly engages a plurality of spoke members, the other ends of which are attached to the hub of the wheel assembly), and a distal surface (i.e., the radially outwardly facing surface with respect to the hub), which is the surface that engages the inner tube or the bead of a tire prior to inflation. The distal surface of the rim has a central hump, a trough contiguous with the central hump extending axially outward from the hump, and a flat shelf immediately adjacent, contiguous with, and extending axially outward from the trough. The rim further includes an integral sidewall extending generally radially outward from an intersection region of the proximal surface and the distal surface of the base portion of the rim. A distal point (i.e., farthest, free end) of the sidewall extends no further than 0.200 in above the shelf of the distal surface of the rim. It will be readily appreciated that the rim consists of two opposing sidewalls and that the distal surface of the base portion consists of a central hump, a trough on each axial side of the hump, and a flat shelf extending axially from each trough out to the intersection region with the proximal surface of the base portion. In an aspect, the distal point of the sidewall extends above the shelf in the range of between about 0.150 in to 0.195 in. In another aspect, the distal point of the sidewall extends only to between about 0.171 in to 0.175 in above the shelf. These

3

dimensional ranges present a sidewall having a height, hereinafter denoted by H, that is on the order of 2 millimeters less than the sidewall height of a conventional bicycle wheel rim. A shorter sidewall as embodied herein not only results in a reduction in the weight of the rim, it also reduces the mechanical leverage that the tire has on the rim, making the rim stiffer and potentially longer lasting by eliminating flexing of the rim, which can lead to cracking. This feature also eliminates the need for corner reinforcement of the rim. Further advantages of a smaller sidewall height include less incidents of pinch flat compared to conventional rims, either with or without tubes, the ability to run lower air pressure in the tire based upon a larger available air volume, and approximately 4 mm more tire surface exposure for improved traction.

According to the embodiments of the invention, the inner profile of the sidewall has substantially the same profile shape as the bead of the tire. This produces a 'ball-and-socket' type fit that helps to reduce strain on the tire bead while creating a tighter air seal. The conventional bead lock at the distal end of the sidewall also has been eliminated. Thus, in an aspect, additional material can be used in the central part of the proximal surface of the rim for added strength and stiffness without increasing the overall weight of the rim.

The hump in the center of the distal surface of the rim is generally convex-shaped, forming an arch-type structure that adds additional strength to the rim. Alternatively, the hump may have a generally flat-top or other shape. The hump does not extend above the shelf of the distal surface as this would make tire mounting difficult. The troughs extending axially away from both sides of the hump provide separate channels for each tire bead. This feature greatly eases the effort of inflation as the separate channels make it easier to trap air. The hump also acts to keep the tire spread apart and allow for the valve stem to inject air directly into the center of the tire.

Another embodiment of the invention is directed to a bicycle wheel, including a rim as outlined above, a plurality of spokes engaged at respective ends thereof with the rim, and a hub engaged with the plurality of spoke members at opposite ends thereof.

Another embodiment of the invention is directed to a bicycle wheel assembly comprising a bicycle wheel as outlined herein above, and a tube and/or tire mounted on the rim.

The foregoing and other objects, features, and advantages of embodiments of the present invention will be apparent from the following detailed description of the preferred embodiments, which makes reference to several drawing figures.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a cross sectional view of an exemplary bicycle wheel rim with an inflatable tire mounted thereon as known in the prior art;

FIG. 2 is a cross sectional view of a bicycle wheel rim according to an embodiment of the invention;

FIG. 3 is a figure identical to FIG. 2 with the addition of a mounted, inflated tire according to an embodiment of the invention;

FIG. 4 is a view identical to that of FIG. 2 showing dimensional indicia according to an exemplary aspect of the invention;

FIG. 5 is a cross sectional view of a bicycle wheel rim according to an exemplary aspect of the invention;

4

FIG. 6 is a cross sectional view of a bicycle wheel rim according to an exemplary aspect of the invention;

FIG. 7 is a cross sectional view of a bicycle wheel rim according to an exemplary aspect of the invention; and

FIG. 8 is a cross sectional view of a bicycle wheel assembly according to an embodiment of the invention.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT OF THE INVENTION

Reference is now made to FIG. 2, which shows a bicycle wheel rim **500** in cross sectional view according to an embodiment of the invention. According to embodiments of the invention, the rim **500** is adaptable for mounting a tubeless tire shown at **600** in FIG. 3 or a tire including an inner tube **610** as illustrated in FIG. 8. As shown in FIG. 1, the rim **500** has a circular base portion **505** having a proximal surface **508** that is engageable with a plurality of spokes **710** (see FIG. 8). The base portion also has a distal surface **511** in opposition to proximal surface **508** that, in part, supports the tube and/or tire. As shown in cross section, the distal surface **511** has a central hump **514**, a trough **517** that is contiguous with the central hump, and a flat shelf **520** immediately adjacent and contiguous with the trough. The rim further has an integral sidewall **530** that extends generally radially upward from an intersecting region **533** of the proximal surface and the distal surface. In all embodiments set forth herein, the sidewall has a height, H, defined as the distance between the surface of the shelf **520** and a distal point **536** of the sidewall **530** that is less than or equal to 0.200 inches. FIG. 4 illustrates the sidewall height, H. The maximum sidewall height, H, is on the order of 2 mm less than the corresponding height of conventional rim sidewalls, which typically ranges between about 0.225 in to 0.265 in and above. The reduced sidewall height as embodied herein provides numerous advantages. For example, less of the tire sidewall is available to exert pressure against the rim sidewall; thus, there is less mechanical leverage exerted by the tire against the rim sidewall. This further results in less flexing of the sidewall particularly in the region designated at **533** in FIG. 2 where cracking and material fatigue may occur. Furthermore, approximately 4 mm more tire surface is available resulting in a larger air volume, the ability to run lower tire pressures, increased traction and reduced incidents of pinch flat or snake-bite puncture. In a particular aspect, the sidewall height, H, is between 0.150 in to 0.195 in. In an exemplary aspect, the sidewall height is between about 0.171 in to 0.175 in.

It will be noted that the distal end **536** of the sidewall **530** does not include a bead lock portion. This is due, in part, to a desirable aspect of the sidewall design; that is, the interior surface profile **542** of the sidewall has a region designated at **541** where the sidewall surface blends to the surface of the flat shelf, that substantially corresponds to a profile shape **650** of the tire bead **620** as illustrated in FIG. 3. This correspondingly similar shape of the sidewall interior surface **541** provides a "ball-and-socket" fit between the sidewall and the tire bead when the tire is fully inflated. The need for a bead lock is thus eliminated and as shown in the figures, the sidewall **530** does not have a bulbous shape at the distal end **536**, as in the prior art of FIG. 1, so that a thickness of the sidewall **530** is not increased from where the sidewall **530** begins to extend inwardly to the distal end **536**. Since weight reduction is always a goal of improved rim design, elimination of the bead lock eliminates the weight associated with them. In an aspect, illustrated in FIG. 6, the weight savings from the bead lock elimination can be

5

redistributed to other regions of the rim for increased strength; for example, the central region **509** of the proximal surface of the rim can be thickened as shown at **510** without increasing the overall weight of the rim. In an exemplary embodiment, the bead seat **520** is disposed horizontally with respect to an axial direction of a rim. FIG. **8** shows such a configuration.

In still another aspect relating to sidewall design, the outer surface of the sidewall can be squared off, for example, as shown at **539** in FIG. **7**.

Referring again to FIG. **2**, in the illustrated aspect, the distal surface **511** is smooth and continuous; i.e., it contains no acute inflection points between the shelves **520**, the troughs **517** or the hump **514**. As further illustrated, the hump has a substantially convex profile. This shape forms an arch structure along the center of the rim surface that contributes to the strength and stiffness of the rim. In an alternative aspect as illustrated in FIG. **5**, the hump may be flat topped as shown at **516** or be otherwise shaped as those skilled in the art will appreciate. As shown in FIG. **4**, a distal point **515** of the hump **514** extends a distance, Y, above the base of the trough **517**. According to an aspect of the embodiment, the value, Y, is between about 0.054 in to 0.062 in. In an exemplary aspect, Y has a value of approximately 0.058 in.

It can be further observed in FIG. **2** that the troughs **517** on opposite axial sides of the hump **514** effectively form two channels. When a tire is initially mounted on the rim, each of the tire beads will sit in a respective trough region **517**. Not only do the hump and troughs serve to keep the tire beads separated and confined prior to and during inflation, the separate channels created by the troughs make it easier to trap air and thus easier to inflate the tire particularly in the case of manual pumping. The hump and troughs also keep the tire spread apart and allow for the valve stem (not shown) to inject the air directly into the center of the tire, easing the inflation process. In an aspect as illustrated in FIG. **4**, the overall trough distance, X, (alternatively, the separation distance between the shelf portions **520**) is between about 0.300 in to 0.700 in. This range of separation distance, X, will accommodate various tire profiles. In a more particular aspect, X is between about 0.535 in to 0.549 in. In an exemplary aspect, X is approximately equal to 0.542 in.

According to another embodiment, illustrated with respect to FIG. **8**, a bicycle wheel **900** includes a rim **500** as described above in all its various aspects, a plurality of spokes **710** engaged at respective ends **711** thereof with the rim and a hub **800** engaged with the plurality of spokes at opposite ends **712** thereof.

In another embodiment, a bicycle wheel assembly includes the wheel **900** as schematically illustrated in FIG. **8** and further includes a tire **600** mounted on the wheel rim. In an aspect, a tube **610** may be used.

The foregoing description of the preferred embodiment of the invention has been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching. It is intended that the scope of the invention be limited not by this detailed description, but rather by the claims appended hereto.

The invention claimed is:

1. A bicycle wheel rim, comprising:
 - a base portion including a proximal surface having a portion that is engageable with a spoke member;

6

flat seats extending around a circumferential direction of the rim so as to support a portion of a tire when the tire is mounted, the seats being horizontally disposed with respect to an axial direction of the rim;

two opposing sidewalls extending from the base portion so that when the tire is mounted, beads of the tire exert pressure that is transferred to the sidewalls and the seats,

a point of each of the sidewalls most distal the flat seats respectively extends no further than 0.200 inches above the flat seats; and

the proximal surface including outer opposing walls that respectively extend from the portion that is engageable with the spoke member, wherein an open space is bound by the outer opposing walls so as to extend from one of the outer opposing walls to the other of the outer opposing walls, the open space curving along a recessed area of the rim.

2. The rim of claim **1**, wherein the sidewalls have an outer surface facing in an outward direction of the rim and an inner surface facing in an inward direction of the rim, at least a portion of the outer surface and the inner surface have the same profile.

3. The rim of claim **1**, wherein the point of each of the sidewalls most distal the seats respectively extends no further than 0.175 inches above the seats.

4. The rim of claim **1**, wherein the recessed area comprises first and second channels separated by a hump.

5. The bicycle wheel rim of claim **1**, wherein the recessed area of the rim is formed between the flat seats, the recessed area having a width between 0.300 and 0.700 inches.

6. The rim of claim **1**, wherein a width of the recessed area is x, where $0.535 \text{ in} < x < 0.549 \text{ in}$.

7. The rim of claim **1**, wherein a bulbous bead lock portion is absent from a distal region of each sidewall.

8. The rim of claim **1**, wherein inner surface profiles of the sidewalls are respectively curved.

9. The rim of claim **1**, wherein the sidewalls respectively bend inwardly toward each other.

10. The rim of claim **1**, wherein each of the sidewalls has an inner surface profile portion that matches a contour of a surface portion of the tire when the tire is engaged.

11. The rim of claim **1**, wherein the outer opposing walls are continuous so as to not contain any acute inflection points.

12. The bicycle wheel rim of claim **1**, wherein a centrally positioned portion of the proximal surface has a material thickness greater than a material thickness of a peripheral region of the proximal surface.

13. A bicycle wheel, comprising:

a plurality of spoke members engaged at respective ends thereof with a rim;

and a hub engaged with the plurality of spoke members at opposite ends thereof, the rim including,

a base portion including a proximal surface having a portion that is engageable with a spoke member;

flat seats extending around a circumferential direction of the rim so as to support a portion of a tire when the tire is mounted, the seats being horizontally disposed with respect to an axial direction of the rim;

two opposing sidewalls extending from the base portion so that when the tire is mounted, beads of the tire exert pressure that is transferred to the sidewalls and the flat seats,

a point of each of the sidewalls most distal the flat seats respectively extends no further than 0.200 inches above the flat seats; and

the proximal surface including outer opposing walls that respectively extend from the portion that is engageable with the spoke member, wherein an open space is bound by the outer opposing walls so as to extend from one of the outer opposing walls to the other of the outer opposing walls, the open space curving along a recessed area of the rim.

14. The bicycle wheel of claim 13, wherein the recessed area of the rim is formed between the flat seats, the recessed area having a width between 0.300 and 0.700 inches.

15. The bicycle wheel of claim 13, wherein the point of each of the sidewalls most distal the seats respectively extends no further than 0.175 inches above the seats.

16. The bicycle wheel of claim 13, wherein a bulbous bead lock portion is absent from a distal region of each sidewall.

17. The bicycle wheel of claim 13, wherein inner surface profiles of the sidewalls are respectively curved.

18. The bicycle wheel of claim 13, wherein the sidewalls respectively bend inwardly toward each other.

19. The bicycle wheel of claim 13, wherein the outer opposing walls are continuous so as to not contain any acute inflection points.

20. The bicycle wheel of claim 13, wherein a centrally positioned portion of the proximal surface has a material

thickness greater than a material thickness of a peripheral region of the proximal surface.

21. The rim of claim 5, wherein the seats are immediately adjacent and contiguous with the recessed area.

22. The bicycle wheel of claim 14, wherein the seats are immediately adjacent and contiguous with the recessed area.

23. The rim of claim 1, wherein the sidewalls extend without increasing in thickness from a midportion of the sidewalls to the point most distal the seats.

24. The bicycle wheel of claim 13, wherein the sidewalls extend without increasing in thickness from a midportion of the sidewalls to the point most distal the seats.

25. The rim of claim 1, wherein the flat seats are disposed beneath the beads of the tire, when the tire is mounted, to form tire bead support sections, such that portions of the rim exist between the tire bead support sections and the recessed area that are not directly beneath the tire beads.

26. The bicycle wheel of claim 13, wherein the flat seats are disposed beneath the beads of the tire, when the tire is mounted, to form tire bead support sections, such that portions of the rim exist between the tire bead support sections and the recessed area that are not directly beneath the tire beads.

* * * * *